



PIN OUT



No	L	CABLE
DW-U5E-0025-GR	250±40mm	CAT. 5E/UTP 26AWG, GREY
DW-U5E-005-GR	500±40mm	CAT. 5E/UTP 26AWG, GREY
DW-U5E-010-GR	1000±40mm	CAT. 5E/UTP 26AWG, GREY
DW-U5E-020-GR	2000±40mm	CAT. 5E/UTP 26AWG, GREY
DW-U5E-030-GR	3000±40mm	CAT. 5E/UTP 26AWG, GREY
DW-U5E-050-GR	5000±100mm	CAT. 5E/UTP 26AWG, GREY
DW-U5E-070-GR	7000±100mm	CAT. 5E/UTP 26AWG, GREY
DW-U5E-100-GR	10000±100mm	CAT. 5E/UTP 26AWG, GREY

NOTES:

1. ELECTRICAL TEST: 100% OPEN, SHORT & MISS WIRE TEST.
2. CONDUCTOR RESISTANCE: 5 OHM MAX
3. INSULATOR RESISTANCE: DC300V/0.01S 500K OHM MIN.
4. PRINTING WORD OF CABLE;

3	Cable	CAT. 5E/UTP CABLE 26AWG(7/0.16)*4P, JACKET: PVC, GREY; OD:5.3±0.2mm	1
2	Molding	45P PVC OUTER MOLDING HOUSING, COLOR:GREY	2
1	Connector	RJ45 MALE CONNECTOR, PIN GOLD PLATED 3U".	2
NO	PART NAME	DESCRIPTION	QTY

-TOLERANCES- UNLESS OTHERWISE SPECIFIED						
	PART DESCRIPTION: Patch Cable CAT5E UTP PVC 3m Gray Non-Snag-Proof					
	P/N: DW-U5E-030-GR					
	Appd: JIM. KING					
UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE: 0.5 - 8mm ± 0.20mm 8 - 30mm ± 0.25mm 30 - 120mm ± 0.30mm	Check:	Date	Scale	Unit	Type	Page
	Draw: Gavin	2022.11.30	Free	MM	Z	1/1