



Keystone module cat. 6 UTP

Keystone cat. 6 UTP

Quick 6



Keystone FibrainDATA Cat.6 UTP with blue anti-dust cover

XQ100.400

WITH BLUE ANTI-DUST COVER



Third Party Testing



Colorful cover



Installation time <1 min

ELECTRICAL AND MECHANICAL PARAMETERS

Maximum current value [A]	1.5
Insulation strength [MOhm] min	500
Contacts resistance [MOhm] max	20
DC Resistance [Ohm] max	0.1
Compliance with the norm	IEC 60603-7 Class E
Compliance with the norm	TIA568-B Cat. 6
Jacket	Non-shielded RJ45 cat. 6
Housing	UL94V-0
Contact material	phosphor-bronze
Contacts	0.46 mm diameter covered with 50 µm gold and 100 µm nickel layer
Jack durability	>750 connection cycles in accordance with EN60603-7
IDC connector	tool-less IDC
Wire diameter	0.4-0.65 mm (AWG26-22)
IDC durability	>200 connection cycles
Coupler material	phosphor-bronze
Coupler coating	1.27 µm silver and 2.5 µm nickel layer
Sequence identification	T568A and T568B

Features

- Tool-less
- Housing minimizes wires unbraiding
- Flame-retardant materials UL94V-0
- Anti-dust cover
- Sequence identification 568A and 568B

Norms

- "Keystone" standard ensures assembly compatibility
- Structured cabling standards ISO/IEC 11801:2011, EN 0173:2011, TIA/EIA568 - C.2
- Verification in accordance with the new standards by independent laboratory centres

Accessories

- **XB-DC-W-01** 25 pcs white anti-dust covers
- **XB-DC-Y-01** 25 pcs yellow anti-dust covers
- **XB-DC-R-01** 25 pcs red anti-dust covers
- **XB-DC-BK-01** 25 pcs black anti-dust covers
- **XT100.KEY** Automatic clamping tool

