

Type:	Outdoor fiber optic cabinets	
Ref:	FDH-E2-x, see ordering information	REV: 1.0
Date:	23.08.2019	DP
Modification:	-	-

FTTH Solutions

Fibrain outdoor fiber optic cabinet FDH-E2



DESCRIPTION:

Fibrain outdoor fiber optic cabinet FDH-E2 ensure very fast installation and distribution of fibers to end users. The casing is made of fire-resistant and self-extinguishing insulating composite, characterized by high resistance to mechanical damage and weather conditions. Thanks to removable, compact design of the internal organizer and the possibility of installing 39 SC SX / LC DX adapters, the cabinet is an ideal solution as a distribution point for FTTH networks. An additional advantage of the cabinet is the door with 180° opening angle which can be disassembled together with the front panels of the housing providing maximum access to its interior.

APPLICATION:

Distribution point of FTTH network;
Local networks;
Last mile networks;
Fiber optic microduct system.

FEATURES & BENEFITS:

Housing material: fibreglass reinforced with polyester;
Removable internal organizer made of galvanized steel;
Dedicated holders for cables / microducts entering the cabinet;
Maximum capacity of 120 splices;
Adapter panel for 39 SC adapters;
Possibility of mounting 3 splitters in Blackbox / Alubox housing;
Possibility of storage up to 5m of cable stock;
Optional separating plate with 3 cable membranes;
Optional lock for front door.

TECHNICAL SPECIFICATION:

Technical data	FDH-E2
Maximum number of splices	120
Maximum number of adapters	39
Adapter type	SC, LC DX
Maximum number of splitters (Blackbox, Alubox)	3
Cabinet dimensions with basis (W)x(H)x(D) [mm]	400x1416x266
Front door dimensions [mm]	456x400
Cabinet height above the ground	756
Flammability class	V0
Internal organizer material	Galvanized steel
Housing material	Fibreglass + polyester
Impact protection	IK10
Ingress protection	IP54

Type:	Outdoor fiber optic cabinets	
Ref:	FDH-E2-x, see ordering information	REV: 1.0
Date:	23.08.2019	DP
Modification:	-	-

Possibility of mounting 3 splitters in Blackbox / Alubox housing

Adapter panel for 39 SC adapters

Separating plate with 3 cable membranes (option)

Holder for cables / microducts entering the cabinet



Removable internal organizer

Maximum capacity of 120 splices
(5 cassettes SCM-A-24H)

Possibility of storage up to 5m of
cable stock

Removable front panels of cabinet

Type:	Outdoor fiber optic cabinets	
Ref:	FDH-E2-x, see ordering information	REV: 1.0
Date:	23.08.2019	DP
Modification:	-	-

FTTH Solutions

ORDERING INFORMATION:

FDH-E2-AABC-DDEFGHH-IJK-LM-N-O-P-RR

Ordering syntax:

AA – Adapter quantity

0 – 39

B – Adapter class

0 – none
1 – Standard One-Piece
2 – Premium One-Piece with internal shutter

C – Adapter type

0 – none
1 – SC/PC
2 – SC/APC
3 – LC/PC
4 – LC/APC

DD – Pigtail quantity

0 – 26

E – Fiber type

A – G.652D
B – G.655
C – G.656
D – G.657A1
E – G.657A2
F – G.657B2
G – G.657B3

F – Connector type

1 – SC/PC
2 – SC/APC
3 – LC/PC
4 – LC/APC

G – Pigtail class

G – Gold

HH- Colour identification

01 – pigtails with yellow 0,9mm buffer
02 – T TELECOM (acc. to IEC60304)

I – Splitter quantity

0– 3

J – Splitter housing

0 – none
1 – Alubox
2 – Blackbox

K – Splitter type

0 – none
1 – 1:2
2 – 1:4
3 – 1:8
4 – 1:16

L – Splice cassette quantity

0 – 5

M – Splice cassette type

0 – none
1 – SCM-A-12H
2 – SCM-A-24H

N – Separating plate

0 – none
1 – equipped

O – Expanded clay

0 – none
1 – equipped

P – Lock

0 – none
1 – equipped

RR – Cabinet colour

GY – grey

Example:

FDH-E2-3912-0000000-000-52-0-1-1-GY

Fibrair outdoor fiber optic cabinet FDH-E2 equipped in 39 adapters SCA Standard class, 5 splice cassettes SCM-A-24H, expanded clay, lock, grey colour.

Important notice

Buyer and/or user of this product has to make sure before using this product that it is suitable for the intended use. All questions of liability relating to this product are subject – in accordance with the prevailing – to the Term of Sale of the selling Fibrain subsidiary.