


Connection components - fiber optic cabling

E-2000™ FIBER OPTIC ADAPTERS



INTRODUCTION:

Fiber optic adapters are designed to combine E-2000™ connectors with a push&pull mechanism, which provides fast and stable connection, and prevents accidental disconnects. The E-2000™ adapter features injection-molded PBT housing, rated to the UL94-V0 flammability index. Spring-loaded laser protection shutters protect against dust and scratching as well as guarantee protection for the eyes. A high quality ceramic alignment sleeve ensures high performance over 1000 mating cycles. Adapters are equipped with a semi-transparent plastic dust cover, providing optical testing with test lasers without removing the cover. The adapters comply with PN/IEC 61754 and DIN/EN 186270 standards.

APPLICATIONS:

- ✓ CATV systems,
- ✓ WDM systems,
- ✓ Metro systems,
- ✓ Active devices,
- ✓ Measurements devices,
- ✓ Telecommunication Networks,
- ✓ Local Area Networks (LANs),
- ✓ Wide Area Networks (WANs),
- ✓ Data and video transmission.

FEATURES:

- ✓ Equipped with integral self-closing metal laser protection internal shutter, which guarantees protection for the eyes and against dust,
- ✓ Excellent optical parameters,
- ✓ Mounting with the use of M2 screws or quick mounting by integrated clip (possibility of flangeless adapter),
- ✓ Constructed from highly resistant and durable PBT material with UL94-V0 flammability index,
- ✓ High quality ceramic alignment sleeve ensures high performance over 1000 mating cycles.

TECHNICAL SPECIFICATION:

Parameter	E-2000™ SM	E-2000™ MM
Insertion Loss (IL)	max. 0.20 dB typ. 0.10 dB	max. 0.30 dB typ. 0.15 dB
Durability	1000 matings/ <0.15 dB typical change	
Strength of coupling mechanism	70N	70N
Alignment sleeve	ceramic	ceramic
Operating temperature	-40 to +85°C	
Internal shutter	✓	✓

Type:	E-2000™ adapters family	REV: 00
Date:	17/12/2014	At
Approved:		BK
Issued::		

Connection components - fiber optic cabling

PACKING SYSTEM:

Adapters are packaged in boxes of 12 pieces in box .

ORDERING INFORMATION:

Code	Adapter type
ADR-E20-SX-1211BL-BL	E2000 SM PC, blue housing, flange, ceramic sleeve
ADR-E20-SX-1211BL-BL-CL	E2000 SM PC, blue housing, no flange, ceramic sleeve
ADR-E2A-SX-1211GR-GR	E2000 SM APC, green housing, flange, ceramic sleeve
ADR-E2A-SX-1211GR-GR-CL	E2000 SM APC, green housing, no flange, ceramic sleeve
ADR-E20-SX-1211BK-BK	E2000 MM PC, black housing, flange, ceramic sleeve

Important notice

Buyer and/or user of this product has to make sure before using this product that it is suitable for the intended use. All questions of liability relating to this product are subject – in accordance with the prevailing – to the Term of Sale of the selling Fibrain subsidiary.