


Installation cable Cat.6_A U/FTP 4PR LSZH CPR Class D_{CA} 500 MHz



CONSTRUCTION:

- 1 – Conductor**
Material: solid bare annealed copper.
Nominal diameter: 23 AWG.
- 2 – Insulation**
Material: Foam skin polyethylene.
Nominal diameter: 1.40 mm.
- 3 – Individual screen:** 2, twisted insulated conductors.
Pair: 4, all twisted together.
Material: aluminum / polyester tape.
- 4 – Outer sheath**
Material: LSZH.
Color: Turquoise (RAL 6027)
- 5 – Drain wire**
Material: tinplated copper wire

Standards

ISO/IEC 11801
EN 50173
IEC 61156-5
EN 50288-10-1
IEC 60332-1-2
IEC 60754-1/2
IEC 61034-1/2

SUPPORTED APPLICATIONS

100BASE-T
1000BASE-T
2,5GBase-T
5GBase-T
10GBase-T
Power over Ethernet

Ordering

XR1281046320– Reel 500m

MECHANICAL CHARACTERISTICS

Min bending radius without a load	4 x D	mm
Min bending radius with a load	8 x D	mm
Max. tensile force	100	N
Weight	47,5	kg/km
Copper content	22,5	kg/km
Outer diameter	6.9	mm
Wire diameter	23	AWG

ELECTRICAL CHARACTERISTICS @ 20°C

Max loop resistance	176	Ω/km
Mutual capacitance	43	nF/km
Nominal velocity of propagation NVP	79	%
Max delay skew	15	ns/100m

This document and the statements contained in it, are not intended for customers within the meaning of Civil Code. The information submitted in this document is to our knowledge and belief true at the time of issue, however, we do not assume any liability whatsoever for its accuracy, and completeness. This document is for informational purposes on an "as is" basis only, and Fibrain reserves the right to change its contents at any time without prior notice. The specification cannot in any case be considered an offer within the meaning of the Civil Code and is not contractually valid unless specifically authorized by Fibrain. Before using this product, its buyer and/or user has to make sure that it is suitable for the intended use. All liability issues related to this product are subjected to the seller's separate Terms of Sale or the terms and conditions agreed with the Fibrain representative or distributor.

Mean characteristic impedance @ 100 MHz	100 ± 5	Ω
Max Transfer impedance @ 1 MHz	50	mΩ/m
@ 10 MHz	100	mΩ/m
@ 30 MHz	200	mΩ/m
Segregation classification acc. EN 50174-2:	C	-
Min coupling attenuation	55	dB

ENVIRONMENTAL CHARACTERISTICS

Temperature range during storage	-20 ÷ +60	°C
Temperature range during operation	-20 ÷ +60	°C
Temperature range during installation	0 ÷ +50	°C

FIRE REACTION

Fire load	570	MJ/km
Jacket material	LSZH acc: IEC 60332-1-2, IEC 60754-1/2; IEC 61034-1/2	
Euroclass acc. CPR (EN 50575)	D_{CA}-s2,d1,a1; DoP 0009P	

NOMINAL TRANSMISSION CHARACTERISTICS

Frequency	Attenuation	NEXT	PS-NEXT	ACR	PS-ACR	ACR-F	PS-ACR-F	RL
MHz	dB/100m	dB	dB	dB/100m	dB/100m	dB/100m	dB/100m	dB/100m
1,0	1,8	100	97	98	95	105	105	-
4,0	3,4	100	97	97	94	105	102	27
10,0	5,4	100	97	95	92	97	94	30
16,0	6,8	100	97	93	90	93	90	30
20,0	7,7	100	97	92	89	91	88	30
31,2	9,6	100	97	90	87	87	84	30
62,5	13,7	100	97	86	83	81	78	30
100,0	17,4	100	97	83	80	77	74	30
125,0	19,5	95	92	75	72	75	72	26
155,5	21,9	94	91	72	69	73	70	26
175,0	23,3	93	90	70	67	72	69	25
200,0	25,0	92	89	67	64	71	68	25
250,0	28,1	90	87	62	59	69	66	24
300,0	30,9	89	86	58	55	67	64	24
500,0	42,0	83	80	41	38	62	59	22

CABLE MARKING

FIBRAIN DATA CABLE CAT6A U/FTP 4PR 23 AWG 500MHZ NVP 79% LSZH CPR CLASS Dca ISO/IEC11801 EN50173 ANSI/TIA/568-C.2 JJJJ XR1281046320 OFRRRRRR . XXXXX M

Where

JJJJ: production year
OFRRRRRR: manufacturer order
XXXXX: length

This document and the statements contained in it, are not intended for customers within the meaning of Civil Code. The information submitted in this document is to our knowledge and belief true at the time of issue, however, we do not assume any liability whatsoever for its accuracy, and completeness. This document is for informational purposes on an "as is" basis only, and Fibrain reserves the right to change its contents at any time without prior notice. The specification cannot in any case be considered an offer within the meaning of the Civil Code and is not contractually valid unless specifically authorized by Fibrain. Before using this product, its buyer and/or user has to make sure that it is suitable for the intended use. All liability issues related to this product are subjected to the seller's separate Terms of Sale or the terms and conditions agreed with the Fibrain representative or distributor.